


Marlow[®] DATASHEET

STANDARD SHOCKCORD

First quality, high elasticity, natural rubber provides a minimum 100% stretch with constant elongation characteristics.

Polyester cover is tough and UV resistant offering good abrasion resistance and a great range of standard colours.



Key Specifications:

Material:	Natural rubber Polyester (continuous filament high or medium tenacity Polyester)
Construction:	Parallel rubber threads core 12-24 Plait (depending on size)
Scope:	Polyester cover cords 3-10mm diameter 100% nominal extension.
Testing Method:	Measure sample length and weight g/m at zero tension Measure 6 point diameter average (no load)
Colours:	Black, white, blue, red and neon yellow

PERFORMANCE

DIAMETER		MASS		MIN LOAD AT 100% ELONGATION			MAX LOAD AT 100% ELONGATION		
mm	Inch	g/m	lb/100 ft	kg	lb	N	kg	lb	N
3	1/8	7	0.47	0.7	1.6	7	1.1	2.5	11
4	5/32	12.5	0.84	1.3	2.9	13	2.0	4.5	20
5	3/16	20.0	1.34	2.0	4.5	20	3.4	7.4	33
6	7/32	33.0	2.21	2.8	6.1	27	4.1	9.0	40
7	1/4	40.0	2.68	3.6	7.9	35	5.1	11.2	50
8	5/16	48.0	3.22	4.9	10.8	48	7.1	15.7	70
10	13/32	77.0	5.16	8.2	18.0	80	12.2	27.0	120

COVER COLOUR	RUBBER THREAD COLOUR
white / black	white
red	black
blue	black
green	black
black	black

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England
www.marlowropes.com

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com



Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

Certificate Number 315
ISO 9001
ISO 14001